Similarity Solutions for the Stagnation-Point Flow and Heat Transfer Over a Nonlinearly Stretching/Shrinking Sheet

(Penyelesaian Keserupaan bagi Aliran Titik Genangan dan Pemindahan Haba terhadap Helaian Meregang/Mengecut)

NORFIFAH BACHOK & ANUAR ISHAK*

ABSTRACT

This paper presents a numerical analysis of a stagnation-point flow towards a nonlinearly stretching/shrinking sheet immersed in a viscous fluid. The stretching/shrinking velocity and the external flow velocity impinges normal to the stretching/shrinking sheet are assumed to be in the form $U \sim x^n$, where m is a constant and x is the distance from the stagnation point. The governing partial differential equations are converted into ordinary ones by a similarity transformation, before being solved numerically. The variations of the skin friction coefficient and the heat transfer rate at the surface with the governing parameters are graphed and tabulated. Different from a stretching sheet, it is found that the solutions for a shrinking sheet are non-unique for m > 1/3.

Keywords: Boundary layer; dual solutions; nonlinear stretching/shrinking, similarity solution

ABSTRAK

Makalah ini melaporkan analisis berangka aliran titik genangan terhadap helaian meregang/mengecut tak linear yang terendam dalam bendalir likat. Halaju regangan/pengecutan dan halaju aliran bebas normal ke arah helaian meregang/mengecut diandaikan dalam bentuk $U \sim x^m$, dengan m adalah pemalar dan x adalah jarak dari titik genangan. Persamaan-persamaan menakluk dalam bentuk persamaan pembezaan separa ditukar kepada persamaan pembezaan biasa menggunakan penjelmaan keserupaan, sebelum diselesaikan secara berangka. Perubahan-perubahan pekali geseran kulit dan kadar pemindahan haba pada permukaan terhadap parameter-parameter terlibat dilaporkan dalam bentuk graf dan jadual. Berbeza dengan kes regangan, didapati bahawa penyelesaian bagi kes pengecutan adalah tidak unik bagi m > 1/3.

Kata kunci: Lapisan sempadan; penyelesaian dual; penyelesaian keserupaan; regangan/pengecutan tak linear

INTRODUCTION

The problem of laminar boundary-layer flow resulting from the flow of an incompressible viscous fluid past a stretching sheet where the velocity on the boundary is away and proportional to the distance from a fixed point, was considered by Crane (1970). Gupta and Gupta (1977) added suction or injection effect on the surface. Wang (1984) obtained similarity solutions to the axisymmetric case. The combination of both stagnation flow and stretching surface was considered by Mahapatra and Gupta (2002, 2003) and was extended to oblique stagnation flow by Lok et al. (2006). The boundary layer flow due to a shrinking sheet has attracted considerable interest recently. There are two conditions that the flow towards the shrinking sheet likely to exist, whether an adequate suction on the boundary is imposed (Miklavčič & Wang 2006) or a stagnation flow is considered (Wang 2008), so that the velocity of the shrinking sheet is confined in the boundary layer. Similar problems with various boundary conditions and in different situations have been considered by Bachok et al. (2010), Fang and Zhang (2009), Ishak et al. (2010), Nadeem and Awais (2008), Sajid and Hayat (2009)).

Vajravelu (2001) studied the flow and heat transfer aspects for the viscous fluid flow over a nonlinearly stretching sheet, but the heat transfer characteristics in this flow was analyzed only in the case when the sheet is kept at a constant temperature. Bataller (2008) extended this problem to two different types of thermal boundary conditions on the sheet, i.e. prescribed surface temperature and prescribed surface heat flux. Different from Vajravelu (2001) and Bataller (2008), we study in this paper the stagnation-point flow toward a nonlinearly stretching/shrinking sheet with velocity $U_w = ax^m$ and free stream velocity $U_\infty = bx^m$, where a, b and m are constants. To the best of the authors' knowledge, this problem has not been studied before and therefore the results obtained are novel. Examples of practical applications of this problem include the polymer melts and solutions, heat treated materials traveling between a feed roll and a wind-up roll or materials manufactured by extrusion, glass-fiber and paper production, cooling of metallic sheets or electronic chips, crystal growing, on a rising, shrinking balloon and many others. In these cases, the final product of desired characteristics depends on the rate of cooling in the process and the process of stretching/shrinking.

PROBLEM FORMULATION

Consider a laminar two-dimensional stagnation flow of a viscous and incompressible fluid normal to a stretching/ shrinking sheet of constant temperature T_w . The boundary layer equations are given by:

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0, \tag{1}$$

$$u\frac{\partial u}{\partial x} + v\frac{\partial u}{\partial y} + U_{\infty}\frac{dU_{\infty}}{dx} + v\frac{\partial^2 u}{\partial y^2},$$
(2)

$$u\frac{\partial T}{\partial x} + v\frac{\partial T}{\partial y} = \alpha \frac{\partial^2 T}{\partial y^2},\tag{3}$$

subject to the boundary conditions:

$$u = U_{w}, v = 0, T = T_{w} \text{ at } y = 0$$

$$u \to U_{\infty}, T \to T_{\infty} \text{ as } y \to \infty,$$
(4)

where u and v are the velocity components along the x and y axes, respectively, T is the fluid temperature in the boundary layer, T_{∞} the ambient temperature, v the kinematic viscosity and α is the thermal diffusivity.

The governing partial differential equations (1)–(3) can be reduced to ordinary differential equations by introducing the following transformation:

$$\eta = \left(\frac{U_{\infty}}{vx}\right)^{1/2} \quad y, \psi = \left(vxU_{\infty}\right)^{1/2} f\left(\eta\right), \quad \theta\left(\eta\right) = \frac{T - T_{\infty}}{T_{w} - T_{\infty}}, \quad (5)$$

where η is the similarity variable and ψ is the stream function defined in the usual way as $u = \partial \psi / \partial y$ and $v = -\partial \psi / \partial x$, which identically satisfies (1).

The transformed ordinary differential equations are:

$$f''' + \frac{m+1}{2} ff'' + m(1 - f'^2) = 0,$$
(6)

$$\frac{1}{\Pr}\theta'' + \frac{m+1}{2}f\theta' = 0,$$
(7)

where primes denote differentiation with respect to η . The boundary conditions (4) now become:

$$f(0) = 0, f'(0) = \varepsilon, \ \theta(0) = 1,$$
 (8)

$$f'(\eta) \to 1, \ \theta(\eta) \to 0 \text{ as } \eta \to \infty,$$

where $\varepsilon = a/b$ is the stretching/shrinking parameter with $\varepsilon > 0$ for stretching and $\varepsilon < 0$ for shrinking.

RESULTS AND DISCUSSION

Numerical solutions to the transformed ordinary differential equations (6) and (7) subjected to the boundary conditions (8) were obtained using a shooting method. The equations were solved for several values of the stretching/shrinking parameter ε and the velocity exponent parameter m, for two values of Prandtl number Pr, namely Pr = 0.7 (air) and Pr = 7 (water). Figures 1 and 2 show the variations of the

reduced skin friction coefficient f''(0) and the reduced heat transfer rate at the surface $-\theta'(0)$ with ε . It is seen that there are regions of unique solutions for $\varepsilon \ge -1.0$, dual solutions for $\varepsilon_c < \varepsilon \le -1.0$ and no solutions for $\varepsilon < \varepsilon_c < -1.0$. Therefore, the solutions exist up to the critical value $\varepsilon_c (\le -1.0)$, beyond which no solution exists. These values of ε_c are given in Table 1. Moreover, as presented in Figures 1 and 2, dual solutions exist for m > 1/3.




FIGURE 1. Skin friction coefficient f''(0) as a function of ε for various values of m




FIGURE 2. Variation of $-\theta'(0)$ with ε for various values of *m* when Pr = 0.7

TABLE 1. The minimum values of ε (i.e. ε_c) for which solution to the system of ordinary differential equations (6) - (8) exists for Pr = 0.7

m	$\boldsymbol{\mathcal{E}}_{c}$
2/3	-1.1652
1	-1.2465
2	-1.3498

Table 2 presents the values of the upper and lower branch of f''(0) and $-\theta'(0)$, which respectively denoted by $f''_u(0), f''_l(0)$ and $-\theta'_u(0), -\theta'_l(0)$ for m = 2/3, 1 and 2 when $\varepsilon = -1.1$ (shrinking case). As discussed by Merkin (1985), Harris et al. (2009) and Weidman et al. (2006), who reported the existence of dual solutions, the upper branch solutions are stable, while the lower branch solutions are not. For the stable solutions, the heat transfer rate at the surface is higher for the stretching case compared to that of shrinking. It is seen in Figure 1 that all curves intersect at a point (1, 0). This is not surprising since there is no shear stress at the surface when the stretching velocity equals the free stream velocity, regardless of the values of *m*. However, as seen in Figure 2, the heat transfer at

the solid-fluid interface still occurs, i.e. $-\theta'(0) \neq 0$, even there is no shear stress for this case ($\varepsilon = 1$), since they are at different temperatures. Moreover, all the solution curves have (-1, 0) as their limit point.

Figures 3 to 6 display the samples of velocity and temperature profiles for different values of m, Pr and ε . These profiles satisfy the far field boundary conditions (8) asymptotically, which support the numerical results, besides supporting the dual nature of the solutions presented in Figures 1 and 2.

TABLE 2. Values of $f''_u(0)$, $f''_l(0)$ and $-\theta'_u(0)$, $-\theta'_l(0)$ for m = 2/3, 1 and 2 when $\varepsilon = -1.1$ (shrinking case) and Pr = 0.7

m	$f_{u}^{\prime\prime}(0)$	$f_l''(0)$	$- heta_{u}^{\prime}\left(0 ight)$	$-\Theta'_l(0)$
2/3	0.8213	0.1455	0.1149	0.0003
1	1.1867	0.0492	0.1828	0.0003
2	1.8719	-0.0898	0.2903	0.0004




FIGURE 3. Velocity profiles $f'(\eta)$ for various values of *m* when $\varepsilon = 1.5$




FIGURE 5. Velocity profiles $f'(\eta)$ for various values of *m* when = -1.15




FIGURE 4. Temperature profiles $\theta(\eta)$ for various values of *m* for Pr = 0.7 and 7.0 when $\varepsilon = 1.5$




FIGURE 6. Temperature profiles $\theta(\eta)$ for various values of *m* for Pr = 0.7 when ε = -1.15

CONCLUSION

Similarity solutions for the problem of stagnation-point flow towards a nonlinearly stretching/shrinking sheet with constant surface temperature were investigated numerically. The governing partial differential equations were converted into ordinary ones by a similarity transformation, before being solved numerically by a shooting method. The variations of the skin friction coefficient and the heat transfer rate at the surface with the governing parameters were obtained and discussed. Different from a stretching sheet, it was found that the solutions for a shrinking sheet are non-unique for m > 1/3. Moreover, for the stable solution, the heat transfer rate at the surface is higher for the stretching case compared to those of shrinking.

ACKNOWLEDGMENTS

The financial support received from the Ministry of Science, Technology and Innovation, Malaysia (Project Code: 06-01-02-SF0610) is gratefully acknowledged.

REFERENCES

- Bachok, N., Ishak, A. & Pop, I. 2010. Melting heat transfer in boundary layer stagnation-point flow towards a stretching/ shrinking sheet. *Physics Letters* A 374: 4075-4079.
- Bataller, R.C. 2008. Similarity solutions for flow and heat transfer of a quiescent fluid over a nonlinearly stretching surface. *Journal of Material Processing and Technology* 203: 176-183.
- Crane, L.J. 1970. Flow past a stretching plate. Zeitschrift für Angewandte Mathematic und Physik 21: 645-647.
- Fang, T. & Zhang, J. 2009. Closed-form exact solutions of MHD viscous flow over a shrinking sheet. *Communications in Nonlinear Science and Numerical Simulations* 14: 2853-2857.
- Gupta, P.S. & Gupta, A.S. 1977. Heat and mass transfer on a stretching sheet with suction and blowing. *Canadian Journal* of Chemical Engineering 55: 744-746.
- Haris, S.D., Ingham, D.B. & Pop, I. 2009. Mixed convection boundary-layer flow near the stagnation point on a vertical surface in a porous medium: Brinkman model with slip. *Transport in Porous Media* 77: 267-285.
- Ishak, A., Lok, Y.Y. & Pop, I. 2010. Stagnation-point flow over a shrinking sheet in a micropolar fluid. *Chemical Engineering Communications* 197: 1417-1427.
- Lok, Y.Y., Amin, N. & Pop, I. 2006. Non-orthogonal stagnation point flow towards a stretching sheet. *International Journal* of Nonlinear Mechanics 41: 622-627.

- Mahapatra, T.R. & Gupta, A.S. 2002. Heat transfer in stagnationpoint flow towards a stretching sheet. *Heat and Mass Transfer* 38: 517-521.
- Mahapatra, T.R. & Gupta, A.S. 2003. Stagnation-point flow towards a stretching surface. *Canadian Journal of Chemical Engineering* 81: 258-263.
- Merkin, J.H. 1985. On dual solutions occuring in mixed convection in a porous medium. *Journal of Engineering Mathematics* 20: 171-179.
- Miklavčič, M. & Wang, C.Y. 2006. Viscous flow due to a shrinking sheet. *Quarterly of Applied Mathematics* 64: 283-290.
- Nadeem, S. & Awais, M. 2008. Thin film flow of an unsteady shrinking sheet through porous medium with variable viscosity. *Physics Letters A* 372: 4965-4972.
- Sajid, M. & Hayat, T. 2009. The application of homotopy analysis method for MHD viscous flow due to a shrinking sheet. *Chaos, Solitons and Fractals* 39: 1317-1323.
- Vajravelu, K. 2001. Viscous flow over a nonlinearly stretching sheet. Applied Mathematics and Computations 124: 281-288.
- Wang, C.Y. 1984. The three-dimensional flow due to a stretching flat surface. *Physics of Fluids* 27: 1915-1917.
- Wang, C.Y. 2008. Stagnation flow towards a shrinking sheet. International Journal of Nonlinear Mechanics 43: 377-382.
- Weidman, P.D., Kubitschek, D.G. & Davis, A.M.J. 2006. The effect of transpiration on self-similar boundary layer flow over moving surface. *International Journal of Engineering Science* 44: 730-737.

Norfifah Bachok Department of Mathematics and Institute for Mathematical Research Universiti Putra Malaysia 43400 UPM Serdang, Selangor D.E. Malaysia

Anuar Ishak*

Centre for Modelling & Data Analysis School of Mathematical Sciences Faculty of Science and Technology Universiti Kebangsaan Malaysia 43600 UKM Bangi Selangor D.E. Malaysia

*Corresponding author; email: anuarishak@yahoo.com

Received: 11 November 2010 Accepted: 14 January 2011